


FLOS

 F1070075 Brick Red

Bellhop Floor

Designed by Edward Barber and Jay Osgerby, 2020

26W - 1023lm - 2700K - CRI> 90




Floor lamp with indirect light. Stem in painted aluminium: shiny white, brick, cioko, green. Reflector in shiny opal white and grey blown glass. Electrical cable of 270 cm usable length with foot dimmer switch for ON/OFF function and brightness adjustment 10–100%. Power supply with interchangeable plugs.

Main specifications


EAN	8059607039717
Mounting	Floor
Environment	Indoor dry location
Light source type	LED
LED type	LED array
Lamp holder	COB LED
Number of heads	1
Power (W)	26
System power (W)	26
System flux (lm)	1023

Physical

Colour	Brick Red
Length (mm)	260
Cord length (mm)	2700
Net weight (kg)	9.82
Package volume (m3)	0.05
IP	20
IP external	20



Schematic light drawing



Beam Angle: 33°

h(m)	E(lx)	D(m)
1	1474	0.59
2	368	1.19
3	164	1.78
4	92	2.38
5	59	2.97

Luminous flux Luminaire
1232 lm

Photometric

Lighting type	Indirect
Light distribution	Roto symmetric
CCT (K)	2700
CRI>	90


Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/48
LED current (mA)	700
Driver	Remote included
Dimmable	Yes
Dimming type	Electronic 12V
Dimming interface	Switch Integrated (Remote Dimmable)
Cord length (mm)	2700
Plug type	Type G, Type A, Type C
Batteries inside	No


Ecodesign and Energy

Labelling

This product contains a light source of energy efficiency class G



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by an end-user