


Bilboquet

Designed by Philippe Malouin, 2023



LED retrofit

Table lamp with adjustable head. Integrated LED bulb and cut-off providing direct lighting. Body made of a special pigmented polycarbonate deriving from a by-product of paper production rather than from petroleum. Adjustability through steel sphere treated with protective layer deposited in PVD. Useful length of the cable 2 mt. The cable can be adjusted and locked in place through a special slit in the base of the lamp. The product has been designed according to the ISCC standards and it is assembled with total absence of glued components so that it can be completely separated for future recyclability.



Main specifications

| Environments | Indoor dry location |
|-------------------|---------------------|
| Light Source Type | Bulb |
| Lamp category | LED retrofit |
| Lamp holders | GU10 |

Physical

| Colour | Sage |
|---------------------|------|
| Length (mm) | 10 |
| Net weight (kg) | 1.8 |
| Package height (mm) | 10 |
| Package width (mm) | 30 |
| Package length (mm) | 38 |
| Package volume (m3) | 0.01 |
| IP internal | 20 |
| IP external | 20 |















https://professional.flos.com/en/global/product/bilboquet-f0995039/

F0995039

Schematic light drawing



| Beam Angle: | | 54° |
|-------------|-------|------|
| h(m) | E(lx) | D(m) |
| 1 | 571 | 1.01 |
| 2 | 143 | 2.02 |
| 3 | 63 | 3.02 |
| 4 | 36 | 4.03 |
| 5 | 23 | 5.04 |

Luminous flux luminaire 615 lm

Photometric

| Lighting type | Direct |
|--------------------|-----------|
| Light distribution | Symmetric |

Electrical

| Insulation class | II | |
|--------------------|-------------------------------------|--|
| Frequency (Hz) | 50/60 | |
| Main voltage (Vac) | 220-250 | |
| Dimmable | No | |
| Dimming interface | Switch Integrated (Not Dimmable) | |
| Plug type | Type C | |