

Clessidra 20°+20°

■ F1583018 - Deep Brown

Diffused direct/indirect-light wall lighting device. Body obtained by means of aluminium pressofusion and diffusers in PMMA. Aluminium wall attachment with cover in PA66. Available in white-painted or chrome-plated for indoor version and dark brown-painted or dark gray-painted for outdoor version. High-efficiency lenses specially designed for the application, non-replaceable. Wide range (100-240Volt) power pack integrated in the body. Level IP55



Main specifications

| | | | |
|------------------------|-------|--------------------|-----------------------------|
| Number of heads | 2 | Environment | Indoor Outdoor wet location |
| Power (W) | 10 | | |
| CCT (K) | 3000K | | |
| Net lumen (lm) | 637 | | |
| Mountings | Wall | | |

Optical

| | |
|---------------------------|------------------|
| Lighting type | Indirect, Direct |
| LED type | LED array |
| Light distribution | Symmetric |
| Optical type | Diffused light |

Electrical

| | | | |
|-----------------------|--------------|-------------------------|---------|
| Frequency (Hz) | 50/60 | Emergency | Without |
| Voltage (V) | 100-240 | Insulation class | I |
| Lamp holder | COB LED | | |
| Driver | Integrated | | |
| Driver type | Non Dimmable | | |

Physical

| | |
|--------------------|------------|
| Color | Deep Brown |
| Weight (kg) | 1.1 |

