# NJP Table

The fixture provides direct glare-free horizontal light while reflecting some of the light through the rear of the head, illuminating the top of the arm. The ergonomic design of the fixture head shapes the light and gives optimal light direction. A simple mechanical system provides great freedom of movement, so the light can always be set in the ideal position in the workspace. The shade is painted white on the inside, reflecting comfortable diffused light.



NJP - Biblioteket Kulturværftet



Set location -

Kanslergade

### Product info

#### Information

Driver fitted externally on cord. The light has two built-in intensities. The weight includes the base plate. The innovation of the LED technology is constant. The specifications mentioned are based on present technology.

#### Mounting

Cord type: Plastic. Cord length: 2m. Switch: On the fixture head. Timer function: 4 hours/8 hours. Table thickness: Ø10 Pin: 12-50mm. Ø40 Pin: 5-35mm. Clamp: up to 45mm. LED driver: separate, plugs into power outlet. The light has two built-in intensities.

#### Finish

White, black, light alu grey or dark alu grey, powder coated.

Materials Base: Steel. Arms and lamp head: Aluminium. Joints: Anodised aluminium.

#### Sizes and weights

Width x Height x Length (mm) | 220 x 480 x 480 Max 5.1 kg

#### Class

Ingress protection IP20. Electric shock protection II w/o ground.

#### Light source

LED 2700K 10W <br />Lumen: 529

#### Information

Driver fitted externally on cord. The light has two built-in intensities. The weight includes the base plate. The innovation of the LED technology is constant. The specifications mentioned are based on present technology.

#### **Product family**



NJP Wall

NJP Floor

### **Product variants**

Colour	Mounting	Cable type	Light source	Lumen
Black	BASE	BLK PL	LED 2700K 10W	529
Dark aluminium grey	CLAMP	WHT PL	LED 3000K 10W	550
Light aluminium grey	PIN Ø10			
O White	PIN Ø40			



## **Product description**

Desk lamp with two degrees of freedom in each hinge/joint

Desk lamp can be ordered with, base, clamp or pin Pin is 10mm and has counter nut to tighten it.

Clamp can be used on table tops up to 45mm in thickness / 1,8"

Desk lamp dimension and degrees of freedom allowing it to provide deliver illumination in accordance with EN 12464

Light source and diffuser positioned recessed into luminaire head to avoid unwanted glare in screens

Luminaire head should have a minimum of two degrees of freedom

Mechanical mowing parts must be able to be tightened using simple ready available tools such as Allen keys, screwdriver.

Luminaire can be ordered in black or white, powder coated Easy to clean

### Mounting

Simple installation Power supply can be separated from cable for conduit routing.

### Light description

Light distribution from luminaire head is a combination of direct and reflected light. Ensuring soft edges on shadow. Lumen package delivers illumination in accordance with EN 12264. Luminaire illuminates itself Asymmetry light distribution achieved by angle of luminaire head LED high efficient COB LED is replaceable A minimum of 50.000h life on driver and LED. LED CC of 2700K and 3000K offered Head functions as heat sink ensuring good heat management LED dimmable (step dimming) Programmable timer function. 4h, 8h and Off setting

### Design

nendo

### Material

Finish is without texture for easy cleaning. Luminaire constructed in aluminium for durability and heat management. Base constructed in steel for higher mass properties

### Weight

Min: 1.221 kg Max: 5.128 kg

### Finish

Black, Dark aluminium grey, Light aluminium grey, White

### Spare parts & accessories

Product	Variant number
NJP TABLE BASE WHT	5744164689
NJP TABLE BASE BLK	5744164692
NJP TABLE CLAMP WHT	5744164702
NJP TABLE CLAMP BLK	5744164715
NJP TABLE PIN Ø10	5744164728
ADAPTOR 12V BLK	5744164867
ADAPTOR 12V WHT	5744164870
NJP TABLE PIN Ø40	5744165170
NJP TABLE BASE DARK GREY	5744165798
NJP TABLE BASE LIGHT GREY	5744165808
NJP TABLE CLAMP DARK GREY	5744165811
NJP TABLE CLAMP LIGHT GREY	5744165824
NJP BUSHING PLAST	5744165183