



Divina Melange 3

Abrasion

Approximately 45.000 Martindale rubs, EN ISO 12947

Pilling

Note 3, EN ISO 12945

Seam slippage

Warp: 2 mm Weft: 2 mm

Lightfastness

Note 5-7 ISO 105-B02

Fastness to rubbing

Dry note 4-5 ISO 105-X12

Wet note 3-5 ISO 105-X12

Absorption

0.60/Class C (flat), 0.70/Class C (waved) EN ISO 354

Airflow

678 Pa s/m EN 29053

Flame resistance

AS/NZS 1530.3, BS 5852 Crib 5, BS 5852 ignition source 3, BS 5852 part 1, BS 5867 part 2 type B, EN 1021-1/2, EN 13501, C-s1, d0, glued, NF D 60 013, NFPA 260, SN 198 898 5.3 with treatment *, UNI 9175 1IM, US Cal. Bull. 117-2013, ÖNORM B1/Q1

* To pass this test flame retardant treatment is necessary. We are looking into more environmental friendly alternatives but for now the external finisher may use a treatment containing halogen based flame retardants

Benefits of wool

Wool is a renewable resource

Wool is very comfortable because of its ability to absorb / give off humidity

Wool is flame retardant

Wool is biodegradable

Wool is naturally soil resistant

Wool ages with grace

Quality benefits

Very good abrasion

Very good lightfastness

Flame retardant

Acoustic performance

Environmental benefits

EU Ecolabel certified

Follow the EU Ecolabel dye restrictions incl. AZO dye and heavy metal restrictions

Complies with REACH regulation

Reduced emissions

Greenguard and Greenguard Gold certified

For further information

kvadrat.dk

Divina Melange 3

Design: Finn Sködt

Type: Upholstery

Composition: 100% new wool

Yarn type: Woollen

Binding: 4-end broken twill

Width: 150 cm

Weight: Approximately 820 g/lin.m

Repeat: None

Cleaning: Vacuuming and dry cleaning.

More info: Maintenance instruction—please see website



10 year warranty   

