

FLOS

F0448009 Off-white


Almendra Arch Suspension Short 2 NEW

Designed by Patricia Urquiola, 2022



2 x 30W - 2700K - CRI > 95

Suspension lamp with diffused light emission available in linear and organic compositions. Tubular structure made of aluminium and CNC aluminium terminals with matte or metallized finish. Edge Lighting technology integrated. Light units can be turned by steps of 60° within the structure in order to change the direction of the light emitted. Metal rosette with matte white finish. The integrated electronics in the ceiling rose allow the use of different dimming systems: 1-10V, DALI, push-dim or potentiometer. Useful length of the cable 3 mt. The product has been designed according to the ISCC standards and it is assembled with total absence of glued components so that it can be completely separated for future recyclability.



Main specifications


EAN	8059607607046
Mounting	Suspension
Environment	Indoor dry location
Light source type	LED
LED type	Edge Lighting
Number of heads	2
Power (W)	30
Source flux (lm)	1170

Physical

Colour	Off-white
Length (mm)	1152
Cord length (mm)	2800
Net weight (kg)	5.85
Package volume (m3)	0.12
IP	20
IP external	20



Schematic light drawing



h(m)	E(lx)	D(m)
1	195	3.17
2	49	6.35
3	22	9.52
4	12	12.69
5	8	15.87

Photometric


Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	95

Electrical


Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Cord length (mm)	2800

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E



Non-replaceable light source



Non-replaceable control gear