## **Ray Floor 2**

by Rodolfo Dordoni , 2006

Floor lamp providing diffused lighting. Steel tube structure, welded, brushed and chrome-plated. Diffuser support in diecast, polished and chrome-plated Zamak alloy. Injectionmolded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injectionmolded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. On the cable there is the electronic dimmer which allows the regulation of light brightness.

Mounting	Floor
Environment	Indoor
Weight	6.2 (met) - 9.2 (glass) Kg
Light sources available	1 x RF26998 LED 21W E27 24521m 3000K CRI80 [e] Dimmable 1 x RF30429 LED 21W E27 22001m 2700K CRI80 [e] Dimmable
Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the regulation of light brightness with a dial.
Dimmer	Included
Voltage	220-240V
Power	MAX 250W
Battery	No
Supply included	Yes
Cord Length	1900 mm
Materials	Aluminum, Glass, Steel
Colors	F5921030 - Black
	F5921009 - White
	F5920020 - Glass



FLC



