





F7541031 Matte Black

To-Tie T1 NEW



Designed by Guglielmo Poletti, 2022




7W - 314lm - 2700K - CRI> 90

Designed by Guglielmo Poletti Table lamp providing diffused light. Clear glass cylindrical lamp body available in multiple sizes. The handle is made of aluminum and also acts as a light emitter. Multi-led diffuser in specially designed white polycarbonate to avoid the Multi Shadow effect and dazzle. High efficiency LED source with a lifetime of more than 50.000 hours. Electric cable of useful length 180 cm, covered in black fabric and equipped with dimmer switch for ON/OFF and adjustment of the light flow between 10-100%. Plug-in power supply with interchangeable plugs. To-Tie is a future-proof lamp as no glue is used to assemble its different parts. The product can therefore be separated, replaced individually, and recycled separately.

Are you a professional and your project needs consulting and support?

**BOOK AN APPOINTMENT** 



### Main specifications

EAN	8059607047613	
Mounting	Table	
Environments	Indoor dry location	
Light Source Type	LED	
LED type	LED Module	
Power (W)	7	
System flux (lm)	314	

### **Physical**

Colour	Matte Black
Length (mm)	210
Net weight (kg)	1.5
Package height (mm)	290
Package width (mm)	295
Package length (mm)	295
Package volume (m3)	0.03
IP internal	20
H2O stop	No

Download  Mounting instructions	<b>业</b> PDF
Photometric Files	<b>⊥</b> ZIP
Technical Drawings	
2D	<b>业</b> ZIP
3D	<b>⊥</b> ZIP

















# 20

### Schematic light drawing



Beam	Angle:	89°
h(m)	E(lx)	D(m)
1	142	1.98
2	35	3.95
3	16	5.93
4	9	7.91
		0 00

h(m)	E(lx)	D(m
1	142	1.98
2	35	3.95
3	16	5.93
4	9	7.91
5	6	9.88

### Photometric

Light distribution	Asymmetric	
CCT (K)	2700	
CRI>	90	

### Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	24
LED voltage Vf (Vdc)	24.00
LED current (mA)	500
Driver	Remote included
Dimmable	Yes
Dimming type	Electronic 24V
Dimming interface	Dimmer Integrated

## **Ecodesign and Energy** Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by an end-



Replaceable control gear by an end-user



00.	Assembly Coaxial Connector	RF3390130
00.	Led Board with connectors for	RF7541200
	To-Tie T1-T2	
01.	Black plug assembly kit & 24V	RF3320100
	driver	
02.	Assembly Body for To-Tie T1	RF7541131
	Black	
03.	Base for To-Tie T1	RF7541100







RF3390130

Assembly Coaxial Connector

RF7541200

Led Board with connectors for To-Tie T1-T2

- CONTRACTOR OF THE PARTY OF TH

RF3320100

Black plug assembly kit & 24V driver

RF7541131

Assembly Body for To-Tie T1 Black



RF7541100

Base for To-Tie T1